



CARATTERISTICHE TECNICHE

- Temperatura di utilizzo:
da -5°C a + 50°C
- Velocità massima di lavoro: 3 Km/h
- Impiego orientativo:
Apparecchiature a traslazione esclusivamente manuale che operano all'interno di edifici come, espositori, attrezzature per ristoranti, carrelli porta oggetti, apparecchiature per ufficio, mobilio medico, elettrodomestici ecc.
- Temono il contatto con idrocarburi, solventi clorurati ed aromatici.

STRUTTURA


- Rivestimento in gomma termoplastica di colore grigio scuro ad **alta conducibilità elettrica** con durezza 93± 3 Shore A.
- Nucleo in polimero termoplastico grigio chiaro ad **alta conducibilità elettrica**.
- Ruota montata su supporto senza parafile di serie (TB/5/8)

TECHNICAL SPECIFICATIONS

- Ambient temperatures:
between -5 and +50°C.
- Maximum speed: 3 Km/h.
- Applications:
Hand-operated equipment for indoor use only on display units, restaurant equipment, trolleys, office equipment, medical equipment, home appliances, etc.
- Not resistant to contact with hydrocarbons, chloride and aromatic solvents.

STRUCTURE

- Dark grey thermoplastic tyre made from **electroconductive materials**. Rubber tyre hardness: 93± 3 Shore A.
- Light grey thermoplastic polymer hub made from **electroconductive materials**.
- Castors are supplied complete without threadguards as standard (TB/5/8).

 TB/5/8

Mozzo con foro passante.

Hub with plain bearing

					
mm	Type	mm	mm	mm	daN
50	TB/5/8	8	21	18	40
60	TB/5/8	10	29	22	60
80	TB/5/8	10	29	24	60
100	TB/5/8	12	34	29	80
125	TB/5/8	12	32	29	80

A RICHIESTA • OPTIONS



TB../1/5/8



con dischi parafile metallici.

Metallic threadguards.